

Interceptor

System Description

The Haltech Interceptor is a totally new "piggy back" ECU designed to work in parallel with your factory ECU.

The Interceptor provides tuning of fuel mixtures, ignition timing, boost levels and many other features with newly designed Interceptor Windows Software. As the Haltech Interceptor works with the factory ECU, you need only tune where necessary, with the factory levels of economy, idle quality, cold start etc being fully maintained.

Performance has never been achieved so quickly, easily and affordable. The Haltech Interceptor has been fully tested on many makes and models, with the range of supported vehicles set to expand rapidly.

Current Supported Vehicles:

Chev/Holden LS1 V8
Ford BA – XR6, XR6T and XR8
Holden VN-VT 5.0L V8/V6
Honda Jazz
Ford EL-AU 5.0L V8/I6
Mini
Mitsubishi EVO 6,7,8
Mitsubishi Magna 3.0/3.5L V6 (Auto and Manual)
Mitsubishi Lancer CC
Nissan Pulsar SR20 N15
Nissan Skyline R32/33
Nissan 200SX SR20DET S14
Nissan 350Z
Subaru WRX MY93-96, MY99-00, MY01 On
Subaru Liberty RS MY89-93, B4 MY01-03, GT MY04 On,
2.5i NA MY04 On, 3.0 H6 MY04 On
Toyota 1J series 1 & 2
Toyota Corolla A112R Sportivo
Toyota Landcruiser MY03 V8
Toyota Wish
Supported models continually updated!

With so many new innovative features, the opposition will be left behind.

**The New Driving Force in
Engine Management**

Specifications

Interceptor Kit Contents:

Interceptor Unit (ECU)
Main Wiring Loom (flying lead)
Programming Software
Instruction Manual on CD

Accessories:

MAP Sensor (1, 2 or 3 bar)
Electronic Boost Bleed Valve
Boost/Fuel/Ignition Trim Module

Fuel/Ignition Tuning

16 load sites * 16 rpm sites
User configurable load and rpm axis sites
-100% to +100% fuel adjustment range with 0.4% resolution
-16 to +16 degree ignition range with 0.25 degree resolution
Dual switch selectable fuel, ignition and boost maps
Tuning done on laptop with fast, intuitive windows graphical software

Physical Specifications

Compact, light weight, high temperature, rugged water proof housing and connectors
Supplied with 1m loom for flexible installation

Feature Highlights

Closed loop boost control with variable boost with RPM (consistent boost levels with varying conditions)
Configurable to user adjustable boost/fuel/ignition trim for user adjustment as required or fast adjustment tuning
Flexible high speed data logging
Configurable to monitor injector duty cycle for safety
Configurable to monitor actual ignition timing for safety

Input/Output Options

4 configurable analogue voltage inputs (can be set to MAP, MAF, TPS, User trim etc.)
3 configurable analogue outputs (can be set to output clamped/intercepted MAF, MAP etc.)
4 configurable digital inputs (can be set to digital/reluctor crank, frequency MAF, user switch, injector DC, ignition timing etc.)
4 configurable digital outputs (can be set to output digital/reluctor crank, frequency MAF, boost control, water spray control etc.)